

Plunge-cut saw with scoring function TSV 60 KEBQ-Plus



Technical data	TSV 60 KEBQ-Plus
Angular range	0 - 45 °
Cutting depth	0 - 62 mm
Dust extraction connection diameter	27/36 mm
Cable length	4 m
Product weight	6 kg

Product highlights

- › With the TSV 60 K, the dream is now a reality. The built-in scorer can be adjusted with precision and, together with the scoring saw blade, it guarantees consistently splinter-free cuts on both sides. Which means perfect sawing results from the very first cut!
- › Whether it's on the construction site or in the workshop, even large panels can be cut with precision. Thanks to Festool system accessories, it cuts just as well as the stationary machine: You can work precisely even while on the move, and can enjoy splinter-free results to suit your needs.
- › The innovative KickbackStop in the plunge-cut saw with scoring function protects your workpiece and minimises the risk of injury. The saw detects a kickback in the blink of an eye and stops the motor within a fraction of a second.












Warranty all-inclusive

The service advantage.

If registration is completed within 30 days of purchase, this tool is fully covered for the first three years

The Festool service terms and conditions shall apply and are available at www.festool.co.uk/service

Plunge-cut saw with scoring function TSV 60 KEBQ-Plus

Accessories	Order no.	Consumable material	Order no.
 Cross-cutting guide rail FSK 250	769941	 Scoring saw blade DIA 47x2,5x6,35 T1	577082
 Cross-cutting guide rail FSK 420	769942	 Saw blade HW 168x1,8x20 PW16	205763
 Cross-cutting guide rail FSK 670	769943	 Saw blade HW 168x1,8x20 W28	205764
 Guide rail FS 1400/2-KP	577043	 Saw blade HW 168x1,8x20 WD42	205765
 Guide rail FS 1900/2-KP	577044	 Saw blade HW 168x1,8x20 TF 52	205766

Main applications

- › Splinter-free cutting of chipboard, specially veneered and plastic-coated panels
- › Splinter-free cutting of HPL compact panels such as Trespa®
- › Precise plunge cuts in materials up to 60 mm thick

