



Revision Date 10-Apr-2024

Version 3 Amended to include NZ Specific Information Per SDS Notice 2017

SAFETY DATA SHEET

1. IDENTIFICATION

Product identifier Product Name EVERCOAT METAL GLAZE ULTRA

Other means of identification

Product Code 100424_100425_800425

Recommended use of the chemical and restrictions on use

Recommended Use Polyester Finishing and Blending Putty. For professional use only.

Uses advised against Uses other than recommended use.

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Evercoat
A division of Illinois Tool Works Inc.
6600 Cornell Road
Cincinnati, OH 45242 USA
513-489-7600

May Also Be Distributed by:

ITW Permatex Canada
101-2360 Bristol Circle
Oakville, ON Canada L6H 6M5
Telephone: (800) 924-6994

May Also Be Imported & Distributed by:

Hindin Marquip Ltd
1012 Great South Road
Penrose 1061, Auckland, New Zealand
Telephone: +64 (0) 9 913 1666

24-hour emergency phone number

NZ POISONS: 0800 POISON 0800 764 766

CHEMTREC: 1-800-424-9300

INTERNATIONAL: 1-703-527-3887

E-mail address: Info@evercoat.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Respiratory sensitization	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1B
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Flammable liquids	Category 3

Label elements

Emergency Overview

Signal word

Danger

Harmful if inhaled
Causes skin irritation
Causes serious eye irritation
May cause allergy or asthma symptoms or breathing difficulties if inhaled
May cause an allergic skin reaction
May cause cancer
Suspected of damaging fertility or the unborn child
May cause respiratory irritation. May cause drowsiness or dizziness
Causes damage to organs through prolonged or repeated exposure
Flammable liquid and vapor

**Appearance** Apple**Physical state** Liquid**Odor** Pungent**Precautionary Statements - Prevention**

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Use only outdoors or in a well-ventilated area
Wash face, hands and any exposed skin thoroughly after handling
In case of inadequate ventilation wear respiratory protection
Contaminated work clothing should not be allowed out of the workplace
Do not breathe dust/fume/gas/mist/vapors/spray
Do not eat, drink or smoke when using this product
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ ventilating/ lighting/ equipment
Use non-sparking tools
Take precautionary measures against static discharge
Keep cool
Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
If skin irritation or rash occurs: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician In case of fire: Use CO₂, dry chemical, or foam to extinguish.

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Toxic to aquatic life with long lasting effects. Harmful to aquatic life.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Polyester Resin	PROPRIETARY	15 - 40
Styrene	100-42-5	10 - 30
Ground Limestone (Calcium Carbonate)	1317-65-3	7 - 13
Talc (hydrous magnesium silicate)	14807-96-6	7 - 13
Magnesite	546-93-0	1 - 5
Titanium Dioxide	13463-67-7	1 - 5
Zinc Phosphate	7779-90-0	1 - 5
Trade Secret	Proprietary	1 - 5

4. FIRST AID MEASURES**Description of first aid measures****General advice**

Get medical advice/attention if you feel unwell.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin contact

IF ON SKIN: Wash skin with soap and water. If skin irritation persists, call a physician. Take off contaminated clothing and wash before reuse.

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.

Ingestion

IF SWALLOWED: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.

Self-protection of the first aider

Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

Most important symptoms and effects, both acute and delayed**Symptoms**

See section 2 for more information.

Indication of any immediate medical attention and special treatment needed**Note to physicians**

Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable extinguishing media**

Carbon dioxide (CO₂), Dry chemical, Foam

Unsuitable extinguishing media

Water

Specific hazards arising from the chemical

Flammable.

Explosion data**Sensitivity to Mechanical Impact** None.**Sensitivity to Static Discharge** None.**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures****Personal precautions** Remove all sources of ignition. Use personal protective equipment as required.**Environmental precautions****Environmental precautions** See section 12 for additional ecological information. Do not flush into surface water or sanitary sewer system.**Methods and material for containment and cleaning up****Methods for containment** Prevent further leakage or spillage if safe to do so.**Methods for cleaning up** Soak up with inert absorbent material.**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.**7. HANDLING AND STORAGE****Precautions for safe handling****Advice on safe handling** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.**Conditions for safe storage, including any incompatibilities****Storage Conditions** Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).**Incompatible materials** Strong oxidizing agents**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Control parameters****Exposure Guidelines**

Chemical Name	NZ WES	ACGIH TLV	OSHA PEL	NIOSH IDLH
Styrene 100-42-5	TWA 20 ppm 85 mg/m ³ STEL 40 ppm 170 mg/m ³	STEL: 40ppm TWA: 20 ppm	TWA: 100 ppm (vacated) TWA: 50 ppm (vacated) TWA: 215 mg/m ³ (vacated) STEL: 100 ppm (vacated) STEL: 425 mg/m ³ Ceiling: 200 ppm	IDLH: 700 ppm TWA: 50 ppm TWA: 215 mg/m ³ STEL: 100 ppm STEL: 425 mg/m ³
Ground Limestone (Calcium Carbonate) 1317-65-3	TWA: 10 mg/m ³	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust

			(vacated) TWA: 5 mg/m ³ respirable fraction	
Talc (hydrous magnesium silicate) 14807-96-6	TWA 2(r)	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	(vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more; use Quartz limit	IDLH: 1000 mg/m ³ TWA: 2 mg/m ³ containing no Asbestos and <1% Quartz respirable dust
Magnesite 546-93-0	TWA: 10 mg/m ³	-	-	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Titanium Dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³ TWA: 2.4 mg/m ³ CIB 63 fine TWA: 0.3 mg/m ³ CIB 63 ultrafine, including engineered nanoscale

NIOSH IDLH *Immediately Dangerous to Life or Health*

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls

Minimize exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin and body protection

Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Respiratory protection

Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Apple
Odor	Pungent
Odor threshold	No information available

	<u>Values</u>	<u>Remarks • Method</u>
Property pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	145 °C / 293 °F	
Flash point	32 °C / 90 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Relative density	0.96	
Water solubility	No information available	
Solubility(ies)	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	
<u>Other Information</u>		
Softening point	No information available	
Molecular weight	No information available	
VOC Content (%)	No information available	
VOC content		
Applied	0.32 lbs/gal	
Packaged	1.15 lbs/gal	
Density	No information available	
Bulk density	No information available	
SADT (self-accelerating decomposition temperature)	No information available	

10. STABILITY AND REACTIVITY

Reactivity

No information available

Chemical stability

Stable under normal conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Excessive heat.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	May cause irritation of respiratory tract.
Eye contact	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
Skin contact	May cause skin irritation and/or dermatitis.
Ingestion	Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Styrene 100-42-5	= 1000 mg/kg (Rat)	> 2000 mg/kg (Rat)	= 11.7 mg/L (Rat) 4 h
Titanium Dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Zinc Phosphate 7779-90-0	> 5000 mg/kg (Rat)	-	-
Trade Secret	= 5410 mg/kg (Rat)	-	-

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Styrene 100-42-5	-	Group 2A	Reasonably Anticipated	X
Talc (hydrous magnesium silicate) 14807-96-6	-	Group 3	-	X
Titanium Dioxide 13463-67-7	-	Group 2B	-	X

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Chronic toxicity May cause adverse liver effects. Contains a known or suspected reproductive toxin.

Target Organ Effects Central nervous system, Central Vascular System (CVS), Eyes, Liver, Lungs, Reproductive System, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 62325 mg/kg

ATEmix (inhalation-dust/mist) 1.8 mg/l

ATEmix (inhalation-vapor) 18.2 mg/l

12. ECOLOGICAL INFORMATION**Ecotoxicity**

22.94938 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
Styrene 100-42-5	2.95

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment methods****Disposal of wastes**

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated packaging

Do not reuse container.

US EPA Waste Number

D001, U002 U166

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Styrene 100-42-5	Toxic Ignitable
Zinc Phosphate 7779-90-0	Toxic

14. TRANSPORT INFORMATION**Note:**

This information is not intended to convey all specific regulatory information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material. The transportation classification provided is based on ITW Evercoat original packaging, which is suitable for domestic ground transportation only.

DOT

UN/ID No UN3269
Proper shipping name: Polyester Resin Kit
Hazard Class 3
Packing Group III

IATA

UN/ID No UN3269
Proper shipping name: Polyester Resin Kit
Hazard Class 3
Packing Group III

IMDG

UN/ID No UN3269
Proper shipping name: Polyester Resin Kit
Hazard Class 3

15. REGULATORY INFORMATION**International Inventories**

TSCA	Complies
DSL/NDL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Styrene - 100-42-5	0.1
Zinc Phosphate - 7779-90-0	1.0

SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Styrene 100-42-5	1000 lb	-	-	X
Zinc Phosphate 7779-90-0	-	X	-	-

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Styrene 100-42-5	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Styrene 100-42-5	Carcinogen
Titanium Dioxide 13463-67-7	Carcinogen
Crystalline Silica (Quartz) 14808-60-7	Carcinogen
Carbon Black 1333-86-4	Carcinogen

New Zealand Regulations: Surface Coatings and Colourants (Flammable, Carcinogenic) Group Standard 2020 HSR002669

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Styrene 100-42-5	X	X	X
Ground Limestone (Calcium Carbonate) 1317-65-3	X	X	X

Talc (hydrous magnesium silicate) 14807-96-6	X	X	X
Titanium Dioxide 13463-67-7	X	X	X
Zinc Phosphate 7779-90-0	X	-	X
Trade Secret	X	-	-
Isopentane 78-78-4	X	X	X
Pigment Green #7 1328-53-6	X	-	X
Carbon Black 1333-86-4	X	X	X
Pigment Blue #15:2 147-14-8	X	-	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

B2 - Flammable liquid, D2A - Very toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 3	Instability 0	-
HMIS	Health hazards 2	Flammability 3	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Revision Date 10-Apr-2024

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

Haztec 2018 Ltd has amended the supplied SDS only to include NZ Specific Contact Information, Workplace Exposure Standard Values and Group Standard Assigned to (Revision Date amended) and takes no responsibility for any other data in this SDS.

End of Safety Data Sheet